



The Triline Automatic cavity slider has been designed for quick and easy installation and requires minimal commissioning. The Automatic Cavity design complies with the Australian standards AS. 142 8-2009 in accessibility for disabled persons and is extremely wheelchair friendly.

The automatic operator is easily removable without the need for access hatches in plaster wall linings. In the event of a power failure, the door can be opened and closed by hand.

**Min Door Weight:** 20kg

**Max Door Weight:** 80kg

**Min Passage Width:** 875mm

**Recommended Max Leaf Height:** 3000mm

**Recommended Leaf Width:** 1500mm

**Application:** Residential, Commercial

N.B. Max door height and width may vary depending on the weight of the door.

## AUTOMATIC CAVITY UNIT

Behind Triline's luxury Auto Cavity Slider design lies advanced magnetic technology for sliding doors and serves as the basis for the Low Energy Mode. The Auto Cavity Slider has an extremely elegant visual appearance in combination with "Soft Motion" safety feature when operated in Low Energy Mode. The door will stop and reverse on light contact.

This system can be supplied with fittings to suit either glass or wooden doors and is an eye-catching and practical feature for private homes, as well as for professional environments such as clinical practices, offices, hotels and the catering sector.

## FEATURES

- > Various mounting options for desired appearance
- > **Multiple automatic activations:** Pushbutton, Radar Motion Detector, Radio Remote Control, Auto Switch, Push & Go, Manual access of door system, and more.
- > **Panel versions:** Full-frameless glass doors, framed glass doors, timber doors, metal doors
- > **Finish:** Full height or standard height units  
Carrying capacity up to 80kg

P: 03 6272 9861 | F: 03 6273 5022 | E: sales@triline.net.au | W: www.triline.net.au

Copyright © Triline Services Tasmania 2016. All Rights Reserved.

Product improvement is a continuous process. Specifications subject to change without notice.